

Dante Solutions

Blustream has the industry's most comprehensive range of Dante converters that deliver unrivalled options for integrators. Whether analogue or digital, XLR, USB or Bluetooth Blustream has the Dante solution for you.

Encoder & Decoders

DA11ADE

Designed to decode unbalanced or balanced 2ch analogue audio from Dante® digital signal



DA11AEN

Designed to encode unbalanced or balanced 2ch analogue audio to Dante® digital signal



DA11USB

Designed to encode 2 channels of USB audio to a Dante® digital signal, and decode a mono Dante® digital signal to USB audio. Selectable USB Type-B and Type -C connections.



DA11ARC

Designed to encode HDMI ARC (Audio Return Channel) 2ch audio to a Dante® digital signal.



DA11XLR

Converts 2 input channels of balanced / unbalanced / MIC audio with switchable 48V Phantom power to Dante® digital audio.



DA22OPT

Designed to both encode 2ch optical S/PDIF audio to a Dante® digital signal, and decode a Dante® digital signal to 2ch optical S/PDIF audio.



DA22DIG

Designed to both encode 2ch analogue or digital audio to a Dante® digital signal, and decode a Dante® digital signal to 2ch analogue and digital audio.



DA44AU

Four input / four output Dante® digital audio converter.



Dante Networked Amplifiers



NPA20DA

2x10W i2D Class D Digital Dante Amplifier



NPA70DA

2x35W Class D Digital Dante Amplifier with 70/100V Constant



NPA100DA

2x50W Amplifier with 70/100V Constant and sub outputs. Dante, HDMI ARC & MIC inputs

Advanced HDMI Switching

with Dolby audio & DTSX audio downmixing via Dante



SW42DA

The SW42DA is a 4-Way HDMI switch that has been designed to breakout, convert, and downmix embedded Dolby Audio or DTS Audio via Dante.

AV over IP including Dante

IP350UHD-TX/R

4K 18Gbps HDMI, Dante audio, bi-directional IR, RS-232 & USB/KVM up to lengths of 100m over standard 1Gb network architecture, or greater distances using the in-built fibre SFP network interface. Includes dedicated RJ45 output for simplified Dante integration.



IP250UHD-TX/RX

4K HDMI distribution, using visually lossless compression technology, delivers HDMI, Bi-directional IR, RS-232 & USB/KVM up to lengths of 100m over standard 1Gb network architecture. Includes dedicated RJ45 output for simplified Dante integration.



Wallplate solutions

DA11ABL-WP-V2

Multi-input / output wall plate to convert Bluetooth and analogue audio within a digital Dante® networked audio system.



DA22XLR-WP-V2

Multi-input / output wall plate to convert analogue audio within a digital Dante® networked audio system.

